



SKYLIGHT

**LED**

LED Highbay Light  
HB-GKDUA Series



### Product characteristics:

- High thermal conductivity die-cast aluminum body passive cooling classic appearance design Black color
- The lens cover is made of optical grade PC material high transmittance illumination uniformity & low glare.
- Select high quality Osram LED and LED driver high stability.
- Lifetime up to 30000 hrs longer than traditional lamp.
- Ingress protection IP65
- Environment Friendly
- Warranty 3 year

### APPLICATION PLACE



Warehouse



Supermarket



Industrial



The bar / Club



TIS 1955-2551



SkyLight Technology International Co.,Ltd.

37/4-5 Moo.4, T.Taykoa, A.Samkhok, Pathumthani 12160, Thailand Tel : 02-1010377-9 Fax : 02-1010380 website : [www.skylight.co.th](http://www.skylight.co.th)





Warehouse



Supermarket



Industrial



The bar / Club

**LED****LED HIGHBAY LIGHT  
HB-GKDUA Series****Product Specification**

Product		HB-50W	HB-100W	HB-150W	HB-200W
Product Code		HB-GKDUA-50W	HB-GKDUA-100W	HB-GKDUA-150W	HB-GKDUA-200W
Electrical Spec	Consumption	50W ± 5%	100W ± 5%	150W ± 5%	200W ± 5%
	Input Voltage	85-265VAC	85-265VAC	85-265VAC	85-265VAC
	Input Current	0.22A@230VAC	0.43A@230VAC	0.65A@230VAC	0.86A@230VAC
	Power Factor	>0.95@230VAC	>0.95@230VAC	>0.95@230VAC	>0.95@230VAC
	Total Harmonic Distortion (THDi)	<20%@230VAC	<20%@230VAC	<20%@230VAC	<20%@230VAC
	LED Module Input Voltage	36-42VDC	36-42VDC	36-42VDC	36-42VDC
	LED Module Input Current	1.4A	2.7A	3.75A	5.1A
	Dimming (Optional)	Dimmable 0/1-10V			
Optical Specs	CCT (Optional)	2700K/3000K/3500K/4000K/4500K/5000K/5500K/6000K/6500K			
	Typical Luminous Flux (lm)	6500	13000	19500	26000
	Typical Color Rendering Index	>80	>80	>80	>80
	Luminous Flux (lm)	6500 ± 5%	13000 ± 5%	19500 ± 5%	26000 ± 5%
	Luminous efficacy (lm/w)	130 ± 5%	130 ± 5%	130 ± 5%	130 ± 5%
	LED Numbers (pcs)	108	108	150	204
	Average Beam Angle (°)	PC lens with 60°, 90° and 120°			
	LED Brand and Type	Orsam 3030			
Others	Operating temperature (°C)	-25°C~+50°C			
	Storage temperature (°C)	-40°C~+40°C			
	LED Life Span	30000Hours			
	IP Class	IP65			
	IK Class	IK08			
	Certificate	CE, ROHS			
	Body Color	Black			
	Dimensions LxWxH or DxH (mm)	250*59	250*59	310*48	350*55
Weight (Kg)	3.23	3.67	5.83	6.01	

